

Tucker-Kirby Co.
 3825 Wilkinson Blvd.
 Charlotte, NC 28208
 704/ 391-9990 Phone
 704/ 394-9274 Fax

Tucker-Kirby Co.
 2601 Noblin Rd.
 Raleigh, NC 27604
 919/ 277-8410 Phone
 919/ 277-8416 Fax

Tucker-Kirby Co.
 2701 Shop Rd.
 Columbia, SC 29209
 803/ 783-8200 Phone
 919/ 783-8439 Fax



COVERAGE FOR COATING OR MEMBRANES

Thickness of Coating Applied (1000 mils = 1 inch)	Coverage per U.S. Gallon 100% Solids System
1/4 inch = 250 mils	6.4 Square Feet
3/16 inch = 187.5	8.5 Square Feet
1/8 inch = 125 mils	12.8 Square Feet
100 mils	16.0 Square Feet
1/16 inch = 62.5 mils	25.5 Square Feet
50 mils	32.0 Square Feet
1/32 inch = 31.25 mils	51.0 Square Feet
20 mils	80.0 Square Feet
1/64 inch = 15.625 mils	102.0 Square Feet
10 mils	160.0 Square Feet
5 mils	320.0 Square Feet
1 mil	1600.0 Square Feet

If coating contains a solvent which will evaporate, thickness of coating will be reduced by same percentage as solvent loss.